

# Product Info

## F12643G

### **300KG GALVANISED BACKSAVER CRANE WITH EXTENDED BOOM**

#### **Backsaver Crane:**

- Max extended height = 1960 vertical 1526 horizontal at 200kg S.W.L
- Min extended height = 1460 vertical 1770 horizontal at 150kg S.W.L
- Max retracted height = 1687 vertical 1126 horizontal at 300kg S.W.L
- Min retracted height = 1300 vertical 1330 horizontal at 250kg S.W.L

#### 8000 Series Brake Winch as supplied:

Model: F18230 Gear Ratio: 5:1 Application: Lifting Rated Capacity: 300kg (2940N) Mass (Winch only): 6kg Type of Brake: Self Actuating Drum Diameter: 50mm Flange Diameter: 130mm Drum Width: 52mm Cable size: Ø5mm Maximum Cable Capacity: 15m x Ø5mm Max. Effort on handle at Rated Load: 26kg Cable Breaking Strain: 1855kg Cable (Galv) as supplied: 7.5m x Ø5mm

#### Notes:

- Recommended for lifting applications.
- Webbing cannot be used on these winches.
- Self actuating brake requires a minimum of 18kg to operate safely.
- Jarrett Winches and Cranes are not designed for the movement of people.



F13643W (300KG BACKSAVER CRANE (WHITE) WITH EXTENDED BOOM)





F12643 (300KG BACKSAVER CRANE WITH EXTENDED BOOM)

#### F12643GR (300KG GALVANISED BACKSAVER CRANE EXTENDED BOOM WITH 7.5M ROPE)



call 1300 135 935