

Product Info

F12643GR

300KG GALVANISED BACKSAVER CRANE ROPE WITH EXTENDED BOOM

Backsaver Crane:

- Max extended height = 1960 vertical
 1526 horizontal at 200kg S.W.L
- Min extended height = 1460 vertical 1770 horizontal at 150kg S.W.L
- Max retracted height = 1687 vertical
 1126 horizontal at 300kg S.W.L
- Min retracted height = 1300 vertical 1330 horizontal at 250kg S.W.L

8000 Series Brake Winch as supplied:

Model: F18235 Gear Ratio: 5:1 Application: Lifting

Rated Capacity: 300kg (2940N)

Mass (Winch only): 6kg
Type of Brake: Self Actuating
Drum Diameter: 50mm
Flange Diameter: 130mm
Drum Width: 52mm
Fibre Rope size: Ø6mm

Maximum Fibre Rope Capacity: 12m x Ø6mm Max. Effort on handle at Rated Load: 26kg

Fibre Rope Breaking Strain: 2050kg Fibre Rope as supplied: 7.5m x Ø6mm

Fastening Device: Snap Hook

Notes:

- Recommended for lifting applications.
- Webbing cannot be used on these winches.
- Self actuating brake requires a minimum of 18kg to operate safely.
- Jarrett Winches and Cranes are not designed for the movement of people.



F13643W (300KG BACKSAVER CRANE (WHITE) WITH EXTENDED BOOM)





F12643 (300KG BACKSAVER CRANE WITH EXTENDED BOOM)

F12643G

(300KG GALVANISED BACKSAVER CRANE WITH EXTENDED BOOM)

