

Product Info

F19001

500KG BACKSAVER CRANE WITH EXTENDED BOOM

Backsaver Crane:

- Max extended height = 1950 vertical 1450 horizontal at 350kg S.W.L
- Min extended height = 1530 vertical 1700 horizontal at 280kg S.W.L
- Max retracted height = 1640 vertical 1060 horizontal at 500kg S.W.L
- Min retracted height = 1330 vertical 1270 horizontal at 400kg S.W.L
- Vertical storage height = 2300

8000 Series Brake Winch as supplied:

Model : F18260 Gear Ratio: 10:1 Application: Lifting Rated Capacity: 500kg (4900N) Mass (Winch only): 6kg Type of Brake: Self Actuating Drum Diameter: 50mm Flange Diameter: 130mm Drum Width: 52mm Cable size: Ø6mm Maximum Cable Capacity: 12m x Ø6mm Max. Effort on handle at Rated Load: 18kg Cable Breaking Strain: 2712kg Cable Galv) as supplied: 7.5m x Ø6mm Fastening Device: Snap Hook

Notes:

- Recommended for lifting applications.
- Webbing cannot be used on these winches.
- Self actuating brake requires a minimum of 18kg to operate safely.
- Jarrett Winches and Cranes are not designed for the movement of people.



F19001CW (500KG BACKSAVER CRANE (WHITE) WITH EXTENDED BOOM)





F19001R (500KG BACKSAVER CRANE EXTENDED BOOM WITH 7.5M ROPE)

F19001CWR (500KG GALVANISED BACKSAVER CRANE WITH EXTENDED BOOM)



 $_{\text{Call}} 1300 \ 135 \ 935$